


# CPF4N



## 4 sq.mm Push in Fuse Terminal Blocks

CP series Push-In Terminal Blocks have a specialised connection system that enables tool less wire connections. Reliable, vibration resistant, gas tight connections are made with inbuilt high quality stainless steel Push in spring clamps.

### TECHNICAL DATA

Rated Voltage	1000 V
Rated Current	10 A
Housing Material	Polymide
Standard Colour	Grey
Product Function	Single Level Fuse
Wire Entry Orientation	Top
Mounting Possibility	DIN 35/DIN 35-15 Rail
Rated Surge Voltage	8 KV
Pollution Degree	3

### CONNECTION DATA

Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>
Conductor Cross Section Stranded max.	4 mm <sup>2</sup>
Conductor Cross Section AWG/Kcmil min	24 AWG
Conductor Cross Section AWG/Kcmil max	10 AWG
Stripping Length	11 mm

### DIMENSIONS

Height	69.2 mm
Height with DIN 35 x 15 mm rail	76.25 mm
Height with DIN 35 x 7.5 mm rail	68.75 mm
Length	70.7 mm
Width (Thickness)	6 mm

### FUSE SPECIFICATIONS

Fuse Type	Cartridge fuse
Fuse Size	5X20 mm

### ORDERING INFORMATION

CAT. NO.	DESCRIPTION	STD. PACK
CPF4N	4 sq.mm Push in Fuse Terminal Block in Grey Colour	50
CPF4NL6-60V	4 sq.mm Push in Fuse Terminal Block with LED (6-60V) in Grey Colour	50
CPF4NL110-240V	4 sq.mm Push in Fuse Terminal Block with LED (110-240V) in Grey Colour	50
CPF4NL110-240VBK	4 sq.mm Push in Fuse Terminal Block with LED (110-240V) in Black Colour	50

### ACCESSORIES

IMAGES	CAT. NO.	DESCRIPTION	STD. PACK
	CA701-1M	Din 35 Rail unslotted 1 meter	50
	CA701-2M	Din 35 Rail unslotted 2 meter	50
	CA701-2M-S	Din 35 Rail slotted 2 meter	50
	CA701-1M-S	Din 35 Rail slotted 1 meter	50
	CA701-15-1M	Din 35 Rail 15 deep unslotted 1 meter	50
	CA701-15-1M-S	Din 35 Rail 15 deep slotted 1 meter	50
	CA701-15-2M	Din 35 Rail 15 deep unslotted 2 meter	50
	CA701-15-2M-S	Din 35 Rail 15 deep slotted 2 meter	50
	CA104	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	CA103	EndClamp in Polyamide suitable for Din 35/Din 35-15 rails	50
	JX4/2	Shorting Link for 6 mm wide TB	100
	JX4/3	Shorting Link for 6 mm wide TB	50
	JX4/4	Shorting Link for 6 mm wide TB	50
	JX4/5	Shorting Link for 6 mm wide TB	50
	JX4/8	Shorting Link for 6 mm wide TB	10
	JX4/10	Shorting Link for 6 mm wide TB	10
	JX4/16	Shorting Link for 6 mm wide TB	10
	MC6	MARKER CARD 6MM PITCH WITH 72 TAGS	10
	SCS0.5/3	Electricians Screwdriver for slotted screws	10


### APPROVALS



### NOTES

The Rated current is with the use of copper (Cu) conductor/Wire  
Flammability Grade V0 as per UL 94

CPF4N



RATINGS AS PER STANDARDS

STANDARDS	IEC 60947-7-1	UL 1059
Conductor Cross Section Stranded min.	0.2 mm <sup>2</sup>	24 AWG
Conductor Cross Section Stranded max.	4 mm <sup>2</sup>	10 AWG
Rated Voltage	1000 V	600 V
Rated Current	10 A	10 A