

MVS SERIES VENTILATION FANS

Our MVS-12 and MVS-14 complete fan assemblies are UL Listed and engineered for high-performance ventilation in commercial and industrial applications. These fans deliver powerful airflow - up to 300 CFM - with efficient, quiet operation and durable construction.

KEY FEATURES

Enclosure:

- Material: 16 GA Steel with black powder-coated finish
- Wiring: Handy box included for convenient electrical connection

Motor:

- Two-speed, UL-Listed
- Input: 115 VAC, 60 Hz, 0.33A
- Sealed ball bearing design for extended life
- Quiet and efficient performance

Airflow:

- High Speed: Up to 300 CFM (Free Air)
- Low Speed: Up to 250 CFM (Free Air)




Blade:

- 5-paddle aluminum construction
- Optimized for maximum airflow and low noise

DIMENSIONS

- Overall Dimensions: 12" Diameter × 5.70" Height
- Cutout Hole Diameter: 9.75"
- Mounting Pattern: Supports both 3-hole and 4-hole mounting
- Compatible Grille: FG-12-W (See Accessories)

DIAGRAMS





CERTIFICATIONS

UL Listed (Entire unit, not just components)

- Tested to:
- ASME A17.1
- UL 508
- CAN/CSA B44.1

